

WHAT IS CLAIMED IS:

1. An office chair caster comprising:

a wheel holder having a first base and a second base oppositely joined together;

5 said first base having a recess disposed thereon, an opening disposed at one side thereof, a rod housing disposed in an interior thereof and a cover plate integrally disposed at a lower portion thereof, said recess provided with a through hole disposed therein, said through hole provided with a plurality of fitting slots disposed on a wall thereof and
10 extending therethrough in communication with said opening, said through hole also provided with a plurality of stop blocks oppositely disposed on an inner wall surface thereof and a plurality of projections oppositely disposed on said inner wall surface thereof;

 said second base having a through hole disposed thereon, a
15 plurality of retaining pieces protruded from one side thereof corresponding to said plurality of fitting slots of said first base, a rod housing disposed in an interior thereof corresponding to said rod housing of said first base and a cover plate integrally disposed at a lower portion thereof, said through hole provided with a plurality of sliding slots disposed on a wall thereof,
20 each of said sliding slots located between every two of said retaining pieces and extending therethrough in communication with said side of said second base that is protruded with said plurality of retaining pieces, said through hole also provided with two engagement grooves oppositely disposed on an inner wall surface thereof, a connecting rod having both
25 ends respectively fixed in said rod housings of said first base and said second base;

a wheel body capable of being mounted between said cover plates

of said first base and said second base;

a spindle seat capable of being combined in said through holes of said first base and said second base, and having a flange disposed at an upper end thereof, a spindle bore disposed in a center thereof, and a
5 plurality of engagement protuberances oppositely disposed on an outer wall surface thereof; and,

a spindle capable of being accommodated in said through holes of said first base and said second base and extending through said spindle bore of said spindle seat, said spindle having a stop flange disposed at a
10 lower end thereof.

2. The office chair caster as claimed in claim 1, wherein said flange of said spindle seat has at least one hole disposed thereon.

15

20

25